

# Search Light FL-2000X

## USER MANUAL





# F8000020




# Catalogue


I	<b>Warning</b> .....	1
II	<b>Statement</b> .....	1
III	<b>Safety Precautions</b> .....	1
IV	<b>Technology Parameter</b> .....	2
V	<b>Warning for Replace Lam</b> .....	3
VI	<b>Warning for Operation</b> .....	4
VII	<b>Sketch map of Connection</b> .....	4
VIII	<b>Menu Function</b> .....	5
IX	<b>Channels Control</b> .....	6

**CAUTION !** Avoid looking directly into the light source  
**EYEDAMAGES !** (meant especially for epileptics) !

 12m CAUTION! BE CAREFUL OF FIRE  
PLEASE FAR FROM TINDER 12M 

**WARNING !**  
MINIMUM DISTANCE OF INFLAMMABLE  
MATERIALS FROM THE SURFACE 12M.  
MAXIMUM TEMPERATURE OF THE  
EXTERNAL SURFACE 100°C.

 Ta=35°C Tc=100°C 

**Warning**

To reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.

Do not spill water or other liquids into or on to your unit.

During long periods of non-use, disconnect the unit's main power.

It should be installed in a well-ventilated place, at a distance of 50 centimeters or more with the walls.

At the same time, please check if the fan and ventilation holes are unobstructed.

**Statement**

The product has perfect performance and integrity packing. All users should be strictly comply with the warning and operating instructions as stated. Or we aren't in charge of any result by misusing. Any damage resulting by misuse is not within the company's warranty. Any fault or problem caused by Note: All information is subject to change without prior notice.

**Safety Precautions**

In order to guarantee the product's life, please don't put in the damp places or even the environment over 40degrees.

Always mount this unit in safe and stable matter.

The qualified professionals are allowed to carry out the lamp installation, operation and maintenance, but they must guarantee to operate in strict accordance with the instructions referred to.

Using lamp, the change rate of Power voltage should be within +10%, If the voltage is too high, it will shorten the light's life; if it's not enough, the lamp will be dark.

Please restart it after turning off light for 20 minutes until full-cooling. Frequent switching will reduce the life span of lamps and bulbs; intermittent use will improve the life of bulbs and lamps.

In order to make sure the product is used well, please read the Manual carefully

We are introducing the new Search Light FL-2000X, with very good affordable prices. And this FL-2000X is suitable for outdoor lighting purposes, these products are provided with a movable head that supports in light reaching a distant area. We provide these lights with the adjustable angle, and this device Search Light FL-2000X single Beam lighting.

**Features:**

Energy saving design  
Excellent illumination  
Longer service life  
User Manual

**Specifications:**

Outdoor Search Light FL-2000X (2000W-7000W)

- 1.Light source: XHA2-7kW
- 2.Be distance :2-6HP
- 3.Waterproof: IP44

**Technical specification:**

Voltage: AC220W 50-60HZ  
Working currency: 11 A  
Light source: XHA2-7kW  
Color Temperature: 6000K  
Cover: Aluminum cover with insulated paint coat  
Waterproof: IP44  
Chassis: Alloy external painting  
Beam Angle: 9degree  
Extend the distance: 3-6HP  
The level of degree: 90-120 degrees  
Horizontal: 110 degree  
Vertical: 40 °  
Packing Size: 73x85x123cm  
Weight: 73kg